

Appln No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

2

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently amended) A method of enabling user interaction with computer software running in a computer system via:

an interface surface containing information relating to the computer software and ~~having coded data indicative of a drawing input field and having disposed therein or thereon coded data at least partially indicative of the drawing input field~~ the interface surface; and

a sensing device which, when placed in an operative position relative to the interface surface, senses at least some of the coded data and uses the sensed coded data to generates indicating data at least partially indicative of the drawing field, using at least some of the sensed coded data, and generates movement data indicative of the sensing device's movement relative to the interface surface;

the method including the steps of, in the computer system:

- (a) receiving the indicating data from the sensing device;
- (b) receiving the movement data from the sensing device, at least part of said movement data representing drawing input by the user;
- (c) identifying the drawing input field at least partially from the indicating data; and
- (d) operating the computer software at least partly in reliance on the ~~movement data~~ drawing input, and in accordance with instructions associated with the drawing input field.

2. (Original) A method according to claim 1, the method further including the steps of, in the computer system, associating the movement data with the drawing field.

3. (Original) A method according to claim 1, including the step of sending, in the computer system, data to the computer software indicative of at least the drawing field.

4. (Original) A method according to claim 2, wherein the drawing field is associated with a visible drawing zone defined on the interface surface.

5. (Original) A method according to claim 1, wherein the coded data includes at least one tag, each tag being indicative of the drawing field.

6. (Original) A method according to claim 5, wherein the tags are also indicative of points within the drawing field.

7. (Original) A method according to claim 6, wherein each of the tags includes: first identity data defining a relative position of that tag; and

Appln No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

3

second identity data identifying the drawing field.

8. (Original) A method according to claim 7, wherein the relative position is defined in relation to the drawing field.

9. (Currently Amended) A method of enabling user interaction with computer software running in a computer system via:

an interface surface containing information relating to the computer software and having coded data disposed therein or thereon, the coded data being at least partially indicative of an identity of the interface surface; and

a sensing device which, when placed in an operative position relative to the interface surface, senses at least some of the coded data and uses the sensed coded data to generates indicating data at least partially indicative of the identity of the interface surface, and generates movement data indicative of the sensing device's movement relative to the interface surface;

the method including the steps of, in the computer system:

- (a) receiving the indicating data from the sensing device;
- (b) receiving the movement data from the sensing device, at least part of the said movement data representing written gesture input by the user;
- (c) performing written gesture recognition in relation to at least some of the movement data; and
- (d) in the event that a written gesture is recognised, operating the computer system in accordance with instructions associated with the written gesture and the interface surface.

10. (Original) A method according to claim 9, wherein the selection gesture includes circumscribing or underlining at least some of the information.

11. (Original) A method according to any one of the preceding claims, wherein the sensing device includes at least one acceleration measuring device for measuring acceleration of the sensing device as it is used to draw the hand-drawn user input onto the surface, the movement data being generated by periodically sampling the acceleration of the sensing device as it is used to draw the hand-drawn user input onto the surface.

12. (Original) A method according to claim 11, further including the step of generating movement data in the form of a locus of the sensing device in relation to the surface, the locus being determined by ascertaining relative displacement of the sensing device.

13. (Original) A method according to claim 12, wherein the relative displacement is obtained by doubly integrating the acceleration with respect to time.

14. (Original) A method according to claim 12 or 13, wherein the acceleration

DI  
Cont

Appin No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

4

measuring device includes one or more accelerometers configured to measure at least two orthogonal components of acceleration.

15. (Original) A method according to any one of claims 1 to 10, wherein position elements are disposed on the interface surface, the sensing device being configured to periodically sense position elements as it is used to draw the hand-drawn user input onto the surface, the method including the step of generating the movement data in the form of a locus of the sensing device in relation to the surface by ascertaining relative displacement of the sensing device over time with respect to at least one of the position elements.

16. (Original) A method according to claim 15, wherein the position elements are disposed on the surface as a regular array of dots, lines or other formations.

17. (Original) A method according to claim 15, wherein the position elements are disposed on the surface stochastically.

18. (Previously Presented) A method according to any one of claims 1 to 10, wherein the movement data is generated by ascertaining relative movement of one or more motion sensing elements rotatably mounted to the sensing device for contact with the surface while the sensing device is used to draw the hand-drawn user input thereon.

19. (Original) A method according to claim 18, wherein the motion sensing elements include one or more rollerballs mounted for rotation within a constraining housing disposed substantially within the sensing device.

20. (Original) A method according to claim 19, wherein components of rotation of the rollerball, due to movement of the sensing device when drawing the hand-drawn user input onto the surface, are periodically measured.

21. (Original) A method according to claim 20, wherein the components of rotation of the rollerball due to movement of the sensing device by the user when drawing the hand-drawn user input onto the surface are measured by means of:

rollers disposed within the constraining housing for rotation, the rollers being configured to be driven by contact with the rotating rollerball; or

optical sensing of rotation of the rollerball with respect to the constraining housing.

22. (Original) A method according to claim 7, wherein the relative position is defined in relation to a plurality of the other tags.

23. (Original) A method according to claim 7, wherein the relative position is defined in relation to the interface surface.

24. (Original) A method according to claim 7, wherein the first identity data identifies stored information defining the relative position, the stored information not being stored on

Appln No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

5

the interface surface.

25. (Original) A method according to claim 24, wherein the first identity data and the second identity data together identify stored information defining the relative position.

26. (Original) A method according to claim 9, wherein the coded data includes at least one tag, each tag being indicative of the drawing field.

27. (Original) A method according to claim 26, wherein the tags are also indicative of points of the interface surface.

28. (Original) A method according to claim 27, wherein each of the tags includes:  
first identity data defining a relative position of that tag; and  
second identity data identifying the interface surface.

29. (Currently Amended) A system for enabling user interaction with computer software running in a computer system via:

an interface surface containing information relating to the computer software and ~~having coded data indicative of a drawing input field and having disposed therein or thereon~~ coded data at least partially indicative of the drawing input field ~~the interface surface~~; and

a sensing device which, when placed in an operative position relative to the interface surface, senses at least some of the coded data and uses the sensed coded data to generates indicating data at least partially indicative of the drawing input field ~~using at least some of the sensed coded data~~, and generates movement data indicative of the sensing device's movement relative to the interface surface;

the computer system being configured to:

- (a) receive the indicating data from the sensing device;
- (b) receive the movement data from the sensing device, at least part of said movement data representing drawing input by the user;
- (c) identify the drawing input field at least partially from the indicating data; and
- (d) operate the computer software at least partly in reliance on the drawing input movement data, and in accordance with instructions associated with the drawing input field.

30. (Original) A system according to claim 29, the computer system further being configured to associate the movement data with the drawing field.

31. (Original) A system according to claim 29, the computer system being configured to send data to the computer software indicative of at least the drawing field.

32. (Original) A system according to claim 30, wherein the drawing field is associated with a visible drawing zone defined on the interface surface.

Appln No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

6

33. (Original) A system according to claim 29, wherein the coded data includes at least one tag, each tag being indicative of the drawing field.

34. (Original) A system according to claim 33, wherein the tags are also indicative of points within the drawing field.

35. (Original) A system according to claim 34, wherein each of the tags includes:  
first identity data defining a relative position of that tag; and  
second identity data identifying the drawing field.

36. (Original) A system according to claim 35, wherein the relative position is defined in relation to the drawing field.

37. (Currently Amended) A system of enabling user interaction with computer software running in a computer system via:

an interface surface containing information relating to the computer software and having coded data disposed therein or thereon, the coded data being at least partially indicative of an identity of the interface surface ~~disposed in or on the interface surface~~; and

a sensing device which, when placed in an operative position relative to the interface surface, senses at least some of the coded data and uses the sensed coded data to generates indicating data at least partially indicative of the identity of the interface surface ~~using at least some of the sensed coded data~~, and generates movement data indicative of the sensing device's movement relative to the interface surface;

the computer system being configured to:

- (a) receive the indicating data from the sensing device;
- (b) receive the movement data from the sensing device, at least part of the said movement data representing written gesture input by the user;
- (c) perform written gesture recognition in relation to at least some of the movement data; and
- (d) in the event that a written gesture is recognised, operate the computer software in accordance with instructions associated with the written gesture and the interface surface.
38. (Previously Presented) A system according to claim 37, wherein the written gesture includes circumscribing or underlining at least some of the information.
39. (Original) A system according to any one of claims 29 to 38, wherein the sensing device includes at least one acceleration measuring device for measuring acceleration of the sensing device as it is used to draw the hand-drawn user input onto the surface, the movement data being generated by periodically sampling the acceleration of the sensing device as it is used to draw the hand-drawn user input onto the surface.

Appln No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

7

40. (Previously Presented) A system according to claim 39, wherein the computer system is configured to generate the movement data in the form of a locus of the sensing device in relation to the surface, the locus being determined by ascertaining relative displacement of the sensing device.

41. (Original) A system according to claim 40, wherein the relative displacement is obtained by doubly integrating the acceleration with respect to time.

42. (Original) A system according to claim 40 or 41, wherein the acceleration measuring device includes one or more accelerometers configured to measure at least two orthogonal components of acceleration.

43. (Previously Presented) A system according to any one of claims 29 to 42, wherein position elements are disposed on the interface surface, the sensing device being configured to periodically sense position elements as it is used to draw the hand-drawn user input onto the surface, the computer system being configured to generate the movement data in the form of a locus of the sensing device in relation to the surface by ascertaining relative displacement of the sensing device over time with respect to at least one of the position elements.

44. (Original) A system according to claim 43, wherein the position elements are disposed on the surface as a regular array of dots, lines or other formations.

45. (Original) A system according to claim 43, wherein the position elements are disposed on the surface stochastically.

46. (Original) A system according to any one of claims 29 to 45, wherein the movement data is generated by ascertaining relative movement of one or more motion sensing elements rotatably mounted to the sensing device for contact with the surface while the sensing device is used to draw the hand-drawn user input thereon.

47. (Original) A system according to claim 46, wherein the motion sensing elements include one or more rollerballs mounted for rotation within a constraining housing disposed substantially within the sensing device.

48. (Original) A system according to claim 47, wherein components of rotation of the rollerball, due to movement of the sensing device when drawing the hand-drawn user input onto the surface, are periodically measured.

49. (Original) A system according to claim 48, wherein the components of rotation of the rollerball due to movement of the sensing device by the user when drawing the hand-drawn user input onto the surface are measured by means of:

rollers disposed within the constraining housing for rotation, the rollers being

Appln No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

8

configured to be driven by contact with the rotating rollerball; or

optical sensing of rotation of the rollerball with respect to the constraining housing.

50. (Original) A system according to claim 35, wherein the relative position is defined in relation to a plurality of the other tags.

51. (Original) A system according to claim 35, wherein the relative position is defined in relation to the interface surface.

52. (Original) A system according to claim 35, wherein the first identity data identifies stored information defining the relative position, the stored information not being stored on the interface surface.

53. (Original) A system according to claim 52, wherein the first identity data and the second identity data together identify stored information defining the relative position.

54. (Original) A system according to claim 37, wherein the coded data includes at least one tag, each tag being indicative of the interface surface.

55. (Original) A system according to claim 54, wherein the tags are also indicative of points on the interface surface.

56. (Original) A system according to claim 55, wherein each of the tags includes:  
first identity data defining a relative position of that tag; and  
second identity data identifying the drawing field.

57. (Currently Amended) A method to enable a user to interact with computer software running in a computer system utilizing a form printed onto a surface, the form including information relating to the computer software, ~~the surface having coded data indicative of~~ and a drawing input field, relating to the computer software and having disposed therein or thereon the surface coded data at least partially indicative of the drawing input field, the method including the steps of:

providing the form to the user;

receiving, in the computer system, indicating data and movement data from a sensing device, the indicating data at least partially indicative of the drawing input field, the movement data indicative of movement of the sensing device relative to the form, device at least part of said movement data representing drawing input by the user, wherein the sensing device, when placed operatively relative to the drawing field, senses at least some of the coded data and uses the sensed coded data to generate the indicating data ~~based at least partially on sensing at least some of the coded data~~ and substantially simultaneously generating the movement data; and

identifying, in the computer system and at least partially from the indicating data,

Appln No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

9

the drawing input field, and

operating the computer software at least partially in reliance on the drawing input movement data and on instructions associated with the drawing input field.

58. (Previously Presented) The method of claim 57, which includes printing the form in response to receiving, in the computer system, a request for the form.

59. (Previously Presented) The method of claim 57, which includes causing the form and the coded data to be printed onto the surface substantially simultaneously.

60. (Previously Presented) The method of claim 57 further including, in the computer system, associating the movement data with the drawing field.

61. (Previously Presented) The method of claim 57, including the step of performing written gesture recognition on at least some of the movement data.

62. (Previously Presented) The method of claim 57 further including the step of, in the computer system, recognizing whether the movement data is indicative of a written gesture drawn on the surface by the user.

63. (Previously Presented) The method of claim 61 wherein, in the event that the written gesture is recognized, operating the computer system in accordance with instructions associated with the written gesture.

64. (Previously Presented) The method of claim 62 wherein the written gesture includes a selection gesture.

65. (Previously Presented) The method of claim 61 wherein the selection gesture includes circumscribing or underlining at least some of the information.

66. (Previously Presented) The method of claim 57, including the step of identifying the user.

67. (Previously Presented) The method of claim 66, wherein the step of identifying the user includes using the movement data.

68. (Previously Presented) The method of claim 66, further including the step of receiving, in the computer system, data indicative of an identity of the user.

69. (Previously Presented) The method of claim 57, further including the step of receiving, in the computer system, data from a memory of the sensing device, the data being indicative of an identity of the user.

70. (Previously Presented) The method of claim 57, including the step of sending, in the computer system, data to the computer software indicative of at least the drawing field.

71. (Previously Presented) The method of claim 57, wherein the drawing field is associated with a visible drawing zone defined on the surface.



Appln No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

10

72. (Previously Presented) The method of claim 57, wherein the sensing device includes at least one acceleration measuring device for measuring acceleration of the sensing device as it is used on the surface, the movement data being generated by periodically sampling the acceleration of the sensing device as it is used on the surface.

73. (Previously Presented) The method of claim 57, further including the step of generating movement data in the form of a locus of the sensing device in relation to the surface, the locus being determined by ascertaining relative displacement of the sensing device.

74. (Previously Presented) The method of claim 73, wherein the relative displacement is obtained by doubly integrating the acceleration with respect to time.

75. (Previously Presented) The method of claim 72, wherein the acceleration measuring device includes one or more accelerometers configured to measure at least two orthogonal components of acceleration.

76. (Previously Presented) The method of claim 57, wherein elements are disposed on the surface, the sensing device being configured to periodically sense the elements as it is used on the surface, the method including the step of generating the movement data by ascertaining relative displacement of the sensing means over time with respect to at least one of the elements.

77. (Previously Presented) The method of claim 76, wherein the elements are disposed on the surface as a regular array of dots, lines or other formations.

78. (Previously Presented) The method of claim 76, wherein the elements are disposed on the surface stochastically.

79. (Previously Presented) The method according to claim 76, wherein the coded data includes the elements.

80. (Previously Presented) The method of claim 57, wherein the movement data is generated by ascertaining relative rotation of one or more motion sensing elements rotatably mounted to the sensing device for contact with the surface while the sensing device is used thereon.

81. (Previously Presented) The method of claim 80 wherein the motion sensing elements include one or more rollerballs mounted for rotation within a constraining housing disposed substantially within the sensing device.

82. (Previously Presented) The method of claim 81, wherein components of rotation of the rollerball, due to movement of the sensing device on the surface, are periodically measured.

DI  
amt

Appln No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

11

83. (Previously Presented) The method of claim 82, wherein the components of rotation of the rollerball due to movement of the sensing device on the surface are measured by means of:

rollers disposed within the constraining housing for rotation, the rollers being configured to be driven by contact with the rotating rollerball; or  
optical sensing of rotation of the rollerball with respect to the constraining housing.

84. (Previously Presented) The method of claim 57, wherein the coded data is indicative of a plurality of positions, in or associated with the drawing field.

85. (Previously Presented) The method of claim 57, wherein the coded data includes a plurality of tags, each of which includes tag data.

86. (Previously Presented) The method of claim 85, including deriving the relative position of at least one tag using at least some of the at least one tag's tag data.

87. (Previously Presented) The method of claim 86, wherein the relative position is defined in relation to one of the group comprising: a plurality of other tags, the surface, the drawing field and a zone associated with the drawing field.

88. (Previously Presented) The method of claim 85, including deriving an identity of the drawing field using at least some of the tag data of at least one tag.

89. (Previously Presented) The method of claim 88, wherein the data from which the identity of the drawing field is derived is the same in all tags of the same drawing field.

90. (Currently Amended) A system for enabling a user to interact with computer software running in a computer system utilizing a form printed onto a surface, the form including information relating to the computer software, ~~the surface having coded data indicative of and a drawing input field, relating to the computer software and having disposed therein or thereon coded data at least partially indicative of the drawing input field~~ the surface, the system including:

a computer system which:

receives indicating data and movement data from a sensing device, the indicating data at least partially indicative of a drawing input field relating to the computer software and the movement data indicative of movement of the sensing device relative to the form, device at least part of said movement data representing drawing input by the user, wherein the sensing device, when placed operatively relative to the drawing field, senses at least some of the coded data and uses the sensed coded data to generate the indicating data based at least partially on sensing at least some of the coded data and substantially simultaneously generate the movement data;

Appln No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

12

identifies, at least partially from the indicating data, the drawing input field, and operates the computer software at least partially based on reliance on the drawing input movement data and instructions associated with the drawing input field.

91. (Previously Presented) The system of claim 90 including a printer for printing the form in response to receiving, in the computer system, a request for the form.

92. (Previously Presented) The system of claim 90 including a printer for printing the form and in which the printer prints the coded data at substantially the same time as the form.

93. (Previously Presented) The system of claim 90 wherein the computer system is configured to associate the movement data with the drawing field.

94. (Previously Presented) The system of claim 90, wherein the computer system is configured to perform written gesture recognition on at least some of the movement data.

95. (Previously Presented) The system of claim 90 wherein the computer system is configured to recognize whether the movement data is indicative of a written gesture drawn on the surface by the user.

96. (Previously Presented) The system of claim 94 wherein the computer system is configured, in the event that the written gesture is recognized, to operate the computer software in accordance with instructions associated with the written gesture.

97. (Previously Presented) The system of claim 95 wherein the written gesture includes a selection gesture.

98. (Previously Presented) The system of claim 97 wherein the selection gesture includes circumscribing or underlining at least some of the information.

99. (Previously Presented) The system of claim 90, wherein the computer system is configured to identify the user.

100. (Previously Presented) The system of claim 99, wherein the computer system is configured to identify the user by using the movement data.

101. (Previously Presented) The system of claim 99, wherein the computer system is configured to receive data indicative of an identity of the user.

102. (Previously Presented) The system of claim 90, wherein the computer system is configured to receive identity data from a memory of the sensing device, the identity data being indicative of an identity of the user.

103. (Previously Presented) The system of claim 90, wherein the computer system is configured to send data to the computer software indicative of at least the drawing field.

104. (Previously Presented) The system of claim 90, wherein the drawing field is

Appln No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

13

associated with a visible drawing zone defined on the surface.

105. (Previously Presented) The system of claim 90 which includes the sensing device.

106. (Previously Presented) The system of claim 105, wherein the sensing device includes at least one acceleration measuring device for measuring acceleration of the sensing device as it is used on the surface, the movement data being generated by periodically sampling the acceleration of the sensing device as it is used on the surface.

107. (Previously Presented) The system of claim 105, wherein the sensing device generates movement data in the form of a locus of the sensing means in relation to the surface, the locus being determined by ascertaining relative displacement of the sensing device.

108. (Previously Presented) The system of claim 107, wherein the relative displacement is obtained by doubly integrating acceleration with respect to time.

109. (Previously Presented) The system of claim 106, wherein the acceleration measuring device includes one or more accelerometers configured to measure at least two orthogonal components of acceleration.

110. (Previously Presented) The system of claim 105, wherein elements are disposed on the surface, the sensing device being configured to periodically sense elements as it is used on the surface, the movement data being generated by ascertaining relative displacement of the sensing means over time with respect to at least one of the elements.

111. (Previously Presented) The system of claim 110, wherein the elements are disposed on the surface as a regular array of dots, lines or other formations.

112. (Previously Presented) The system of claim 110, wherein the elements are disposed on the surface stochastically.

113. (Previously Presented) The system of claim 110 wherein the coded data includes the elements.

114. (Previously Presented) The system of claim 105, wherein the movement data is generated by ascertaining relative movement of one or more motion sensing elements rotatably mounted to the sensing device for contact with the surface while the sensing device is used thereon.

115. (Previously Presented) The system of claim 114, wherein the motion sensing elements include one or more rollerballs mounted for rotation within a constraining housing disposed substantially within the sensing device.

116. (Previously Presented) The system of claim 115, wherein components of rotation of the rollerball, due to movement of the sensing device when used on the surface, are

DI  
CMT

Appln No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

14

periodically measured.

117. (Previously Presented) The system of claim 116, wherein the components of rotation of the rollerball due to movement of the sensing device by the user when used on the surface are measured by means of:

rollers disposed within the constraining housing for rotation, the rollers being configured to be driven by contact with the rotating rollerball; or  
optical sensing of rotation of the rollerball with respect to the constraining housing.

118. (Previously Presented) The system of claim 90, wherein the coded data is indicative of a plurality of positions in or associated with the drawing field.

119. (Previously Presented) The system of claim 90, wherein the coded data includes a plurality of tags, each of which includes tag data.

120. (Previously Presented) The system of claim 119, wherein the computer system is configured to derive the relative position of at least one tag using at least some of the tag data of the at least one tag.

121. (Previously Presented) The system of claim 120, wherein the relative position is defined in relation to one of the following group: a plurality of other tags, the surface, the drawing field, and a zone associated with the drawing field.

122. (Previously Presented) The system of claim 118, where the computer system is configured to derive an identity of the drawing field using at least some of the tag data of at least one tag.

123. (Previously Presented) The system of claim 122, wherein the data from which the identity of the drawing field is derived is the same in all the tags of the same drawing field.

124. (Previously Presented) The system of claim 105 wherein the sensing device includes a marking nib.

125. (Previously Presented) The system of claim 105 wherein the sensing device contains identity information which imparts a unique identity to the sensing device.

126. (Previously Presented) The system of claim 125 when dependent on claim 102, wherein the identity data includes the identity of the sensing device.

127. (New) The method of claim 1 or claim 9, the sensing device generating at least the movement data in accordance with movement of the sensing device with respect to the coded data.

128. (New) The method of claim 1 or claim 9, the method including printing the interface surface with a printer.

129. (New) The method of claim 1 or claim 9, the indicating data representing at least an

D1  
Cont

Appln No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

15

identity of the interface surface, the method including identifying the drawing input field in the computer system by:

determining the identity of the interface surface;  
using the identity to determine a description of the interface surface; and,  
identifying the drawing input field from the description and at least the movement data.

130. (New) The system of claim 29 or claim 37, the sensing device generating at least the movement data in accordance with movement of the sensing device with respect to the coded data.

131. (New) The system of claim 29 or claim 37, the system including a printer for printing the interface surface.

132. (New) The system of claim 29 or claim 37, the indicating data representing at least an identity of the interface surface, the method including identifying the drawing input field in the computer system by:

determining the identity of the interface surface;  
using the identity to determine a description of the interface surface; and,  
identifying the drawing input field from the description and at least the movement data.

133. (New) The method of claim 57, the sensing device generating at least the movement data in accordance with movement of the sensing device with respect to the coded data.

134. (New) The method of claim 57, the method including printing the surface with a printer.

135. (New) The method of claim 57, the indicating data representing at least an identity of the surface, the method including identifying the drawing input field in the computer system by:

determining the identity of the interface surface;  
using the identity to determine a description of the surface; and,  
identifying the drawing input field from the description and at least some of the movement data.

136. (New) The system of claim 90, the sensing device generating at least the movement data in accordance with movement of the sensing device with respect to the coded data.

137. (New) The system of claim 90, the system including a printer for printing the surface.

Appln No. 09/575,172  
Amdt. Dated February 10, 2004  
Response to Office action of October 21, 2003

16

138. (New) The system of claim 90, the indicating data representing at least an identity of the surface, the method including identifying the drawing input field in the computer system by:

determining the identity of the surface;

using the identity to determine a description of the surface; and,

identifying the drawing input field from the description and at least the movement

data.

*DI  
could*